

陶瓷滤波器 (CERAMIC FILTER)

Series	Center Freq. (KHz)	6dB Band Width (KHz) min	50dB Band Width (KHz) max.	Insertion Loss (dB) max.	Ripple (dB) max.	Attenuation		I/O Impedance (Ω)
						fo \pm 100KHz (dB) min.	40 (W)	
B	fo \pm 2.0	\pm 15	\pm 30	4.0	2.0	28 (U)	40 (W)	1500
C	fo \pm 2.0	\pm 12.5	\pm 24	4.0	2.0	28 (U)	40 (W)	1500
D	fo \pm 1.5	\pm 10	\pm 20	6.0	2.0	28 (U)	40 (W)	1500
E	fo \pm 1.5	\pm 7.5	\pm 15	6.0	2.0	28 (U)	40 (W)	1500
F	fo \pm 1.5	\pm 6	\pm 12.5	6.0	2.0	28 (U)	40 (W)	2000
G	fo \pm 1.5	\pm 4.5	\pm 10	6.0	2.0	28 (U)	40 (W)	2000
HT	fo \pm 1.0	\pm 3	\pm 9	6.0	2.0	35 (U)	60 (W)	2000
I	fo \pm 1.0	\pm 2	\pm 7.5	6.0	2.0	28 (U)	40 (W)	2000

