

陶瓷滤波器 (CERAMIC FILTER)

| Series | Center Freq. (KHz) | 6dB Band Width (KHz) min | 50dB Band Width (KHz) max. | Insertion Loss (dB) max. | Ripple (dB) max. | Attenuation | | I/O Impedance (Ω) |
|--------|-----------------------|-----------------------------|-------------------------------|-----------------------------|---------------------|---------------------------|--------|-------------------------------|
| | | | | | | fo \pm 100KHz (dB) min. | 40 (W) | |
| B | fo \pm 2.0 | \pm 15 | \pm 30 | 4.0 | 2.0 | 28 (U) | 40 (W) | 1500 |
| C | fo \pm 2.0 | \pm 12.5 | \pm 24 | 4.0 | 2.0 | 28 (U) | 40 (W) | 1500 |
| D | fo \pm 1.5 | \pm 10 | \pm 20 | 6.0 | 2.0 | 28 (U) | 40 (W) | 1500 |
| E | fo \pm 1.5 | \pm 7.5 | \pm 15 | 6.0 | 2.0 | 28 (U) | 40 (W) | 1500 |
| F | fo \pm 1.5 | \pm 6 | \pm 12.5 | 6.0 | 2.0 | 28 (U) | 40 (W) | 2000 |
| G | fo \pm 1.5 | \pm 4.5 | \pm 10 | 6.0 | 2.0 | 28 (U) | 40 (W) | 2000 |
| HT | fo \pm 1.0 | \pm 3 | \pm 9 | 6.0 | 2.0 | 35 (U) | 60 (W) | 2000 |
| I | fo \pm 1.0 | \pm 2 | \pm 7.5 | 6.0 | 2.0 | 28 (U) | 40 (W) | 2000 |

1.2 ± 0.1 1.2 ± 0.1

